

# PRODUCTS: LED FLOOD LIGHT SERIES



# LED FLOOD LIGHT SERIES



IL-LED-FL-1 SERIES



The IL-LED-FL-1 SERIES is an energy saving, RGB LED based, wash fixture, incorporating 36 RGB Power LEDs the IL-LED-FL-1 SERIES produces full color 16.7M true 24 Bit color changing effects for architectural and decorative illumination.

The IL-LED-FL-1 SERIES can be operated standalone, master slave with built in pre-programmed effects or directly with and standard DMX-512 controller. The IL-LED-FL-1 SERIES is engineered with push button waterproof external LED display based user interface for setting the mode of operation or DMX Address. The IL-LED-FL-1 SERIES used only 3 Channels of DMX to enable external programming of linear color changing, step based scenes as desired by the lighting designer. You can also add an easy to use pre-programmed external controller if you are DMX challenged such as the Impact Lighting Inc's standalone DMX Controller. For more information on controller functionality refer to the control section of this catalog.

The IL-LED-FL-1 SERIES housing is composed of Aluminum Die Cast fixture housing, heat treated glass aperture plate, rated at IP65.



IL-LED-FL-2 SERIES



The IL-LED-FL-2 SERIES is an energy saving, RGB LED based, wash fixture, incorporating 360 RGB Ultra Bright LEDs the IL-LED-FL-2 produces full color 16.7M true 24 Bit color changing effects for architectural and decorative illumination.

The IL-LED-FL-2 can be operated standalone, master slave with built in pre-programmed effects or directly with and standard DMX-512 controller. The IL-LED-FL-2 is engineered with push button waterproof external LED display based user interface for setting the mode of operation or DMX Address. The IL-LED-FL-2 used only 3 Channels of DMX to enable external programming of linear color changing, step based scenes as desired by the lighting designer. You can also add an easy to use pre-programmed external controller if you are DMX challenged such as the Impact Lighting Inc's standalone DMX Controller. For more information on controller functionality refer to the control section of this catalog.

The IL-LED-FL-2 housing is composed of Aluminum Die Cast fixture housing, heat treated glass aperture plate, rated at IP65.